TRACELINK UNIVERSITY

Home
Resources
TraceLink University

Purchase order acknowledgment inbound Link Action Transactions

The Link Action Purchase Order Ack (PO) in an ERP system is sent by a supplier to confirm receipt of a purchase order and to indicate acceptance, rejection, or modification of the order. This acknowledgment is imported into the ERP system to update the status of the PO and align expectations for delivery, pricing, or availability.

Creatio ERP

The following are the Creatio ERP attributes that are mapped with the Canonical attributes and their output path.

- **Transform Name**:
  - STD_Transform_MPL_Creatio_PurchaseOrderAck_IB_V1

Guidelines

Input Element	Output Path	Output Element	Mapping Rules
Id	-	-	-
Number	data/messageBody/canonicalPurchaseOrderHeader/transactionReferenceIdentifierList	b2bTransactionIdentifierValue	Store literal value where 'b2bTransactionIdentifierType="SUPPLIERORDER
Date	data/messageBody/canonicalPurchaseOrderHeader/transactionReferenceIdentifierList	transactionDate	Store literal value Where'b2bTransactionIdentifierType= PURCHASEORDER and Store literal value where 'b2bTransactionIdentifierType="SUPPLIERORDER
	data/messageBody/canonicalPurchaseOrderHeader/mpcDates	dateValue	Store literal value where dateType=PURCHASEORDER
DueDate	data/messageBody/canonicalPurchaseOrderHeader/mpcDates	dateValue	Store literal value where dateType=DELIVERYREQUESTED
ActualDate	-	-	-
CurrencyRate	-	-	-
Amount	data/messageBody/canonicalPurchaseOrderSummary	summaryValue	Store literal value where summaryType=TOTALAMOUNT
PaymentAmount	-	-	-
PrimaryAmount	-	-	-
PrimaryPaymentAmount	-	-	-
Notes	-	-	-
DeliveryAddress	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	address1	if UsrEDIShipToAddress is not emptymove UsrEDIShipToAddress to target else ifAccount.Address is not emptymoveAccount.Address to target else if DeliveryAddress is not emptymoveDeliveryAddresss to target

© TraceLink Inc. 2009 - 2025 All Rights Reserved

tracelink
NETWORK FOR GREATER GOOD

Input Element	Output Path	Output Element	Mapping Rules
DevatisCustomerPurchaseOrderNumber	data/messageBody/canonicalPurchaseOrderHeader/transactionReferenceIdentifierList	b2bTransactionIdentifierValue	Store literal value where 'b2bTransactionIdentifierType="PURCHASEORDER
DevatisMemo	-	-	-
DevatisEDILocDescription	data/messageBody/canonicalPurchaseOrderHeader/deliveryTerms	description	Store literal value.
DevatisEDITerms	-	-	-
	#data/messageBody/canonicalPurchaseOrderHeader/termsOfPayment	numberOfDays	DevatisEDITerms3% 51 Net 75store value of 4th place in this field .Store literal value
	#data/messageBody/canonicalPurchaseOrderHeader/termsOfPayment	termsOfPaymentPercent	DevatisEDITerms3% 51 Net 75store value of 1st place in this field .Store literal value
	#data/messageBody/canonicalPurchaseOrderHeader/termsOfPayment	discountDueNumberOfDays	DevatisEDITerms3% 51 Net 75store value of 2nd place in this field .Store literal value
UsrAckCodeId	-	-	-
UsrEstimatedDeliveryDate	data/messageBody/canonicalPurchaseOrderHeader/mpcDates	dateValue	Store literal value where dateType=ESTIMATEDDELIVERY If inbound payload has has 0001-01-01T00:00:00Z value then do not map.
UsrRequestedShipDate	data/messageBody/canonicalPurchaseOrderHeader/mpcDates	dateValue	Store literal value where dateType=SHIPPED If inbound payload has has 0001-01-01T00:00:00Z value then do not map.
UsrAutoNumber	-	-	-
UsrEDIPoTypeId	-	-	-
UsrEDIShipToCountry	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	country	ifUsrEDIShipToCountryis not emptymove UsrEDIShipToCountryto target else if Account.CountyCode is not emptymove Account.CountyCode pto target
UsrEDIShipToPostal	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	postalCode	ifUsrEDIShipToPostalis not emptymove UsrEDIShipToPostalto target else if Account.Zip is not emptymove Account.Zip to target
UsrEDIShipToState	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	state	ifUsrEDIShipToState is not emptymove UsrEDIShipToStateto target else if Account.RegionCode is not emptymove Account.RegionCode to target
UsrEDIShipToCity	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	city	if UsrEDIShipToCity is not emptymove UsrEDIShipToCityto target else if Account.CityName is not emptymove Account.CityName to target
UsrEDIShipToAddress	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	address1	if UsrEDIShipToAddress is not emptymove UsrEDIShipToAddress to target else ifAccount.Address is not emptymoveAccount.Address to target else if DeliveryAddress is not emptymoveDeliveryAddresss to target
UsrEDIBillToPostal	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/address	postalCode	Store literal value.If values is empty pick value from DevatisParentAccount.Zip
UsrEDIBillToCountry	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/address	country	Store literal value.If values is empty pick value from DevatisParentAccount.CountryCode
UsrEDIBillToState	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/address	state	Store literal value.If values is empty pick value from DevatisParentAccount.RegionCode
UsrEDIBillToCity	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/address	city	Store literal value.If values is empty pick value from DevatisParentAccount.CityName
UsrEDIBillToAddress	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/address	address1	Store literal value.If values is empty pick value from DevatisParentAccount.Address
UsrEDICancelIfNotDeliveredDate	data/messageBody/canonicalPurchaseOrderHeader/mpcDates	dateValue	Store literal value where dateType=CANCELBY
UsrEDIOrderExpiredDate	-	-	-
UsrBillToPostal	-	-	-
UsrEDIAckAction	-	-	-
Name	data/messageBody/canonicalPurchaseOrderHeader	processingFunctionTypeCode	Convert from source payload to target canonical using enum mapping worksheet: If source = "00", move "CREATE" to target If source = "01", move "CANCEL" to target If source = "04", move "CHANGE" to target If source = "06", move "CONFIRM" to target. If source = "CO", move "CORRECTION" to target
UsrEDIParentIDNumber	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	If UsrEDIParentIDNumber is not empty move UsrEDIParentIDNumber to target else if DevatisParentAccount.UsrNumber is not empty move DevatisParentAccount.UsrNumber to target else if DevatisParentAccount.DevatisIdentificationNumber is not empty move DevatisParentAccount.DevatisIdentificationNumber to target
UsrEDIParentIDType	-	-	-
Description	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/mpcCompanyLocationIdentifierList	companyIdentifierType	if UsrEDIParentIDType.Description is not empty move UsrEDIParentIDType.Description to target else if DevatisParentAccount.DevatisIdentifcationType is not empty Move DevatisParentAccount.DevatisIdentifcationType to target
UsrEDICustomerIDNumber	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	If UsrUsrEDICustomerIDNumber is not empty move UsrEDICustomerIDNumberto target else if Account.UsrNumber is not empty move Account.UsrNumber to target else if Account.DevatisIdentificationNumber is not empty move Account.DevatisIdentificationNumber to target
UsrEDICustomerIDType	-	-	-
Description	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/mpcCompanyLocationIdentifierList	companyIdentifierType	if UsrEDICustomerIDType.Description is not empty move UsrEDICustomerIDType.Description to target else if Account.DevatisIdentifcationType is not empty Move Account.DevatisIdentifcationType to target
Account	-	-	-
Id	-	-	-
Name	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation	businessName	Store literal value.
Code	-	-	-
Phone	-	-	-
AdditionalPhone	-	-	-
Fax	-	-	-
Web	-	-	-
AddressTypeId	-	-	-
Address	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	address1	if UsrEDIShipToAddress is not emptymove UsrEDIShipToAddress to target else ifAccount.Address is not emptymoveAccount.Address to target else if DeliveryAddress is not emptymoveDeliveryAddresss to target
CityName	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	city	if UsrEDIShipToCity is not emptymove UsrEDIShipToCityto target else if Account.CityName is not emptymove Account.CityName to target
RegionCode	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	state	ifUsrEDIShipToState is not emptymove UsrEDIShipToStateto target else if Account.RegionCode is not emptymove Account.RegionCode to target
Zip	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	postalCode	ifUsrEDIShipToPostalis not emptymove UsrEDIShipToPostalto target else if Account.Zip is not emptymove Account.Zip to target
CountryCode	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/address	country	ifUsrEDIShipToCountryis not emptymove UsrEDIShipToCountryto target else if Account.CountyCode is not emptymove Account.CountyCode pto target
DevatisCustomerNumber	-	-	-
DevatisIdentificationNumber	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	If UsrUsrEDICustomerIDNumber is not empty move UsrEDICustomerIDNumberto target else if Account.UsrNumber is not empty move Account.UsrNumber to target else if Account.DevatisIdentificationNumber is not empty move Account.DevatisIdentificationNumber to target

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Input Element	Output Path	Output Element	Mapping Rules
DevatisIdentificationTypeId	-	-	-
DevatisIdentificationType	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/mpcCompanyLocationIdentifierList	companyIdentifierType	if UsrEDICustomerIDType.Description is not empty move UsrEDICustomerIDType.Description to target else if Account.DevatisIdentifcationType is not empty Move Account.DevatisIdentifcationType to target
UsrNumber	data/messageBody/canonicalPurchaseOrderHeader/shipToLocationInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	If UsrUsrEDICustomerIDNumber is not empty move UsrEDICustomerIDNumberto target else if Account.UsrNumber is not empty move Account.UsrNumber to target else if Account.DevatisIdentificationNumber is not empty move Account.DevatisIdentificationNumber to target
DevatisParentAccount	-	-	-
Id	-	-	-
Name	data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation	businessName	Store Literal Value
	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation	businessName	Store Literal Value
Code	-	-	-
Phone	-	-	-
AdditionalPhone	-	-	-
Fax	-	-	-
Web	-	-	-
AddressTypeId	-	-	-
Address	data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation	address1	Store Literal Value.
CityName	data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation	city	Store Literal Value
RegionCode	data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation	state	Store Literal Value
Zip	data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation	postalCode	Store Literal Value
CountryCode	data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation	country	Store Literal Value
Notes	-	-	-
AlternativeName	-	-	-
DevatisPMTTermsId	-	-	-
DevatisCustomerNumber	-	-	-
DevatisIdentificationNumber	data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	if DevatisParentAccount.UsrNumber is not empty move DevatisParentAccount.UsrNumber to target else if DevatisParentAccount.DevatisIdentificationNumber is not empty move DevatisParentAccount.DevatisIdentificationNumber to target
	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	If UsrUsrEDIParentIDNumber is not empty move UsrEDIParentIDNumberto target else if DevatisParentAccount.UsrNumber is not empty move DevatisParentAccount.UsrNumber to target else if DevatisParentAccount.DevatisIdentificationNumber is not empty move DevatisParentAccount.DevatisIdentificationNumber to target
DevatisIdentificationTypeId	-	-	-
DevatisIdentificationType	data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation/mpcCompanyLocationIdentifierList	companyIdentifierType	Store literal value
	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/mpcCompanyLocationIdentifierList		if UsrEDIParentIDType.Description is not empty move UsrEDIParentIDType.Description to target else if DevatisParentAccount.DevatisIdentifcationType is not empty Move DevatisParentAccount.DevatisIdentifcationType to target
UsrNumber	data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	if DevatisParentAccount.UsrNumber is not empty move DevatisParentAccount.UsrNumber to target else if DevatisParentAccount.DevatisIdentificationNumber is not empty move DevatisParentAccount.DevatisIdentificationNumber to target
	data/messageBody/canonicalPurchaseOrderHeader/billToBusinessInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	If UsrUsrEDIParentIDNumber is not empty move UsrEDIParentIDNumberto target else if DevatisParentAccount.UsrNumber is not empty move DevatisParentAccount.UsrNumber to target else if DevatisParentAccount.DevatisIdentificationNumber is not empty move DevatisParentAccount.DevatisIdentificationNumber to target
	#/data/controlFileHeader	fileReceiverNumber	DevatisParentAccount.DevatisIdentificationType +":"+ .DevatisParentAccount.UsrNumber
Currency	-	-	-
Id	-	-	-
Name	-	-	-
Description	-	-	-
Code	-	-	-
ShortName	-	-	-
	data/messageBody/canonicalPurchaseOrderItemDetails/orderPricing	currencyCode	Store literal value.
Symbol	-	-	-
DevatisLocEDI	-	-	-
Id	-	-	-
Name	data/messageBody/canonicalPurchaseOrderHeader/deliveryTerms	fobTransferLocation	If Name =DE then fobTransferLocation should be SHIPPINGDESTINATION and Hard Code deliveryChargePaymentMethodType=PP Else do not map, Hard Code
Description	-	-	-
UsrEDIPoType	-	-	-
Id	-	-	-
Name	data/messageBody/canonicalPurchaseOrderHeader/	purchaseOrderType	Get canonical code from enum list
Description	-	-	-
UsrAckCode	-	-	-
Id	-	-	-
Name	-	-	-
Description	-	-	-
UsrCanonicalCode	data/messageBody/canonicalPurchaseOrderHeader	acknowledgmentType	Store literal value
UsrShipper	-	-	-
Id	-	-	-
Name	data/messageBody/canonicalPurchaseOrderHeader/shipFromLocationInformation	businessName	Store literal Value
Code	-	-	-
Phone	-	-	-
AdditionalPhone	-	-	-
Fax	-	-	-
Web	-	-	-
AddressTypeId	-	-	-
Address	data/messageBody/canonicalPurchaseOrderHeader/shipFromLocationInformation	address1	Store literal Value
CityName	data/messageBody/canonicalPurchaseOrderHeader/shipFromLocationInformation	city	Store literal Value
RegionCode	data/messageBody/canonicalPurchaseOrderHeader/shipFromLocationInformation	state	Store literal Value
Zip	data/messageBody/canonicalPurchaseOrderHeader/shipFromLocationInformation	postalCode	Store literal Value
CountryCode	data/messageBody/canonicalPurchaseOrderHeader/shipFromLocationInformation	country	Store literal Value
DevatisCustomerNumber	-	-	-
DevatisIdentificationNumber	data/messageBody/canonicalPurchaseOrderHeader/shipFromLocationInformation	companyIdentifierValue	If UsrShipper.UsrNumber is not empty move UsrShipper.UsrNumber totarget else ifUsrShipper.DevatisIdentificationNumber is not empty move UsrShipper.DevatisIdentificationNumber to target
DevatisIdentificationTypeId	-	-	-
DevatisIdentificationType	data/messageBody/canonicalPurchaseOrderHeader/shipFromLocationInformation	companyIdentifierType	Store Literal Value
UsrNumber	data/messageBody/canonicalPurchaseOrderHeader/shipFromLocationInformation	companyIdentifierValue	If UsrShipper.UsrNumber is not empty move UsrShipper.UsrNumber totarget else ifUsrShipper.DevatisIdentificationNumber is not empty move UsrShipper.DevatisIdentificationNumber to target

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Input Element	Output Path	Output Element	Mapping Rules
UsrSupplier	-	-	-
Id	-	-	-
Name	data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation	businessName	Store literal Value
Code	-	-	-
TypeId	-	-	-
Phone	-	-	-
AdditionalPhone	-	-	-
Fax	-	-	-
Web	-	-	-
AddressTypeId	-	-	-
Address	data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation	address1	Store literal Value
CityName	data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation	city	Store literal Value
RegionCode	data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation	state	Store literal Value
Zip	data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation	postalCode	Store literal Value
CountryCode	data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation	country	Store literal Value
DevatisCustomerNumber	-	-	-
DevatisIdentificationNumber	data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation	companyIdentifierValue	If UsrSupplier.UsrNumber is not empty move UsrSupplier.UsrNumber totarget else ifUsrSupplier.DevatisIdentificationNumber is not empty move UsrSupplier.DevatisIdentificationNumber to target
	#/data/controlFileHeader	fileSenderNumber	UsrSupplier.DevatisIdentificationType +":"+ .UsrSupplier.UsrNumber
DevatisIdentificationTypeId	-	-	-
DevatisIdentificationType	data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation	companyIdentifierType	Store Literal Value
UsrNumber	data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation	companyIdentifierValue	If UsrSupplier.UsrNumber is not empty move UsrSupplier.UsrNumber totarget else ifUsrSupplier.DevatisIdentificationNumber is not empty move UsrSupplier.DevatisIdentificationNumber to target
	#/data/controlFileHeader	fileSenderNumber	UsrSupplier.DevatisIdentificationType +":"+ .UsrSupplier.UsrNumber
OrderProduct	-	-	-
Id	-	-	-
ProductId	-	-	-
DeliveryDate	-	-	-
Quantity	data/messageBody/canonicalPurchaseOrderItemDetails/itemQuantity	quantityValue	Store literal Value where quantityType=ITEM
UnitId	-	-	-
PrimaryPrice	-	-	-
Price	data/messageBody/canonicalPurchaseOrderItemDetails/orderPricing	pricingAmount	Store literal Value Where pricingType=UNIT
PrimaryAmount	-	-	-
Amount	-	-	-
PrimaryDiscountAmount	-	-	-
DiscountAmount	-	-	-
DiscountPercent	-	-	-
PrimaryTaxAmount	-	-	-
TaxAmount	-	-	-
PrimaryTotalAmount	-	-	-
TotalAmount	-	-	-
DiscountTax	-	-	-
UsrAckCode	-	-	-
Name	#data/messageBody/canonicalPurchaseOrderItemDetails/lineItemAcknowledgment [0]	lineItemStatus	If source ACK01 = "BP", hardcode "PARTIALSHIPMENT" to target. If source ACK01 = "IA", hardcode "ACCEPTED" to target. If source ACK01 = "IC", hardcode "ACCEPTEDWITHCHANGES" to target. If source ACK01 = "ID", hardcode "DELETED" to target. If source ACK01 = "IB", hardcode "BACKORDERED" to target. If source ACK01 = "IH", hardcode "ONHOLD" to target. If source ACK01 = "IP", hardcode "PRICECHANGED" to target. If source ACK01 = "IQ", hardcode "QUANTITYCHANGE" to target. If source ACK01 = "IR", hardcode "REJECTED" to target. If source ACK01 = "IS", hardcode "SUBSTITUTION" to target. If source ACK01 = "R1", hardcode "REJECTEDNOTCONTRACTITEM" to target. If source ACK01 = "R2", hardcode "REJECTEDINVALIDPRODUCT" to target. If source ACK01 = "R3", hardcode "REJECTEDINVALIDUNIT" to target. If source ACK01 = "R4", hardcode "NOTAVAILABLE" to target. If source ACK01 = "SP", hardcode "SCHEDULEDATEPENDING" to target. Map to 0th element
CurrencyRate	-	-	-
BaseQuantity	-	-	-
Unit	-	-	-
Id	-	-	-
Name	-	-	-
Description	-	-	-
ShortName	data/messageBody/canonicalPurchaseOrderItemDetails/itemQuantity	unitOfMeasure	Store literal value if present.
Product	-	-	-
Id	-	-	-
Name	data/messageBody/canonicalPurchaseOrderItemDetails/productItemInformation	productDescription	Store literal value if present.
Code	data/messageBody/canonicalPurchaseOrderItemDetails/productCodesIdentifiers	productCodeValue	Store literal value. Where productCodeType=US_NDC542
UnitId	-	-	-
CurrencyId	-	-	-
Price	-	-	-
Active	-	-	-
ProductSourceId	-	-	-
IsArchive	-	-	-
DevatisPackage	-	-	-
DevatisFormId	-	-	-
DevatisGTIN2	-	-	-
DevatisGTIN1	-	-	-
DevatisMinimumOrderQuantity	-	-	-
DevatisSAP	-	-	-
DevatisUPC	-	-	-
DevatisProductFamilyId	-	-	-

SAP HANA ERP

The following are the Sap Hana ERP attributes that are mapped with the Canonical attributes and their output path.

- **Transform Name**:

© TraceLink Inc. 2009 - 2025 All Rights Reserved

- STD_LA_MPL_Sap_Hana_PurchaseOrderAck_IB_V1

Guidelines

Input Element	Output Path	Output Element	Mapping Rules
SalesOrder	-	-	-
SalesOrderType	-	-	-
SalesOrganization	#/data/messageBody/canonicalPurchaseOrderHeader/supplierBusinessInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	"Store literal value. where companyIdentifierType=COMPANYID"
	#/data/controlFileHeader	fileSenderNumber	"COMPANYID +"":""+ .SalesOrganization "
DistributionChannel	-	-	-
OrganizationDivision	-	-	-
SoldToParty	#/data/messageBody/canonicalPurchaseOrderHeader/customerBusinessInformation/mpcCompanyLocationIdentifierList	companyIdentifierValue	"Store literal value. where companyIdentifierType=COMPANYID"
	#/data/controlFileHeader	fileReceiverNumber	COMPANYID +":"+ .SoldToParty
CreationDate	#/data/messageBody/canonicalPurchaseOrderItemDetails/mpcDates	dateValue	" Store literal value. where DateType=PURCHASEORDER If inbound payload has has 0001-01-01T00:00:00Z value then do not map. Milliseconds will be rounded off 000. "
	#/data/messageBody/canonicalPurchaseOrderHeader/transactionReferenceIdentifierList	transactionDate	"Store literal value. where b2bTransactionIdentifierType=PURCHASEORDER If inbound payload has has 0001-01-01T00:00:00Z value then do not map. Milliseconds will be rounded off 000. "
	-	epochTransctionDate	
PurchaseOrderByCustomer	#/data/messageBody/canonicalPurchaseOrderHeader/transactionReferenceIdentifierList	b2bTransactionIdentifierValue	"Store literal value. where b2bTransactionIdentifierType=PURCHASEORDER "
TotalNetAmount	#/data/messageBody/canonicalPurchaseOrderSummary	summaryValue	"Store literal value if present. where summaryType=TOTALAMOUNT"
TransactionCurrency	#/data/messageBody/canonicalPurchaseOrderHeader/mpcCurrency	currencyCode	Store literal value if present.
CustomerPaymentTerms	#/data/messageBody/canonicalPurchaseOrderHeader/termsOfPayment	description	Store literal value, if present.
Items	-	-	-
SalesOrderItem	#/data/messageBody/canonicalPurchaseOrderItemDetails	lineItemNumber	-
Material	#/data/messageBody/canonicalPurchaseOrderItemDetails/productCodesIdentifiers	productCodeValue	"Store literal value. Where productCodeType=MANUFACTURER"
	canonicalPurchaseOrder/messageBody/canonicalPurchaseOrderItemDetails/productItemInformation	productName	Store literal value.
RequestedQuantity	#/data/messageBody/canonicalPurchaseOrderItemDetails/itemQuantity	quantityValue	"Store Literal Value. where quantityType=ITEM"
	canonicalPurchaseOrder/messageBody/canonicalPurchaseOrderItemDetails/deliverySchedule	scheduledQuantity	Store Literal Value.
RequestedQuantityUnit	#/data/messageBody/canonicalPurchaseOrderItemDetails/itemQuantity	unitOfMeasure	"Store Literal Value. where quantityType=ITEM"
OrderQuantityUnit	-	-	-
OrderQuantitySAPUnit	-	-	-
ItemTransactionCurrency	#/data/messageBody/canonicalPurchaseOrderItemDetails/orderPricing	currencyCode	"Store literal value if present with pricingType = ""NET"" If ItemTransactionCurrency is not empty move ItemTransactionCurrencyt to target else if PricingCurrencyis not empty move PricingCurrency to target "
NetAmount	#/data/messageBody/canonicalPurchaseOrderItemDetails/orderPricing	pricingAmount	Store literal value with pricingType = "NET"
Batch	-	-	-
ProductionPlant	#data/messageBody/canonicalPurchaseOrderItemDetails	plantIdentifier	"If ProductionPlant is not empty move ProductionPlant to target else if OriginalPlant is not empty move OriginalPlant to target "
OriginalPlant	#data/messageBody/canonicalPurchaseOrderItemDetails	plantIdentifier	"If ProductionPlant is not empty move ProductionPlant to target else if OriginalPlant is not empty move OriginalPlant to target "
StorageLocation	-	-	-
WBSElement	-	-	-
PricingElement	-	-	-
ConditionType	-	-	-
ConditionAmount	-	-	-
PricingCurrency	#/data/messageBody/canonicalPurchaseOrderItemDetails/orderPricing	currencyCode	"Store literal value if present with pricingType = ""NET"" and ConditionType = 'PPR0' If ItemTransactionCurrency is not empty move ItemTransactionCurrencyt to target else if PricingCurrencyis not empty move PricingCurrency to target "

Review TraceLink's **API: Terms of Use**

Related Content

Forecast plan (IDoc)

Forecasting APIs allow companies to exchange data about anticipated product demand and supply availability with upstream supply chain Partners without giving these Partners access to their serialization system of record.

View More

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Forecast plan (X12)

Forecasting APIs allow companies to exchange data about anticipated product demand and supply availability with upstream supply chain Partners without giving these Partners access to their serialization system of record.

View More



Forecast plan response (IDoc)

Forecasting APIs allow companies to exchange data about anticipated product demand and supply availability with downstream supply chain Partners without giving these Partners access to their serialization system of record.

View More

© TraceLink Inc. 2009 - 2025 All Rights Reserved