TRACELINK UNIVERSITY

List APIs

Companies that own or link to Agile Process Teams use these APIs to add, edit, and delete lists. A List is a multi-enterprise business object that allows to group multiple Items, Work Items, and sub-types. Owners can collaborate internally or externally with Partners to meet to track and complete a series of tasks (items, work items, and subtypes) in a list required to achieve a business objective.

Add list

Owners and Partners use this API to add a new list to the Owner's company network, including any initial comments or file attachments. The response returns a generated identifier for the new list.

New tasks are assigned the `Draft` base state by default.

Contact your TraceLink Services representative for more information about using this API.

Add list request

Guidelines

Element	Type	Description
mutation ListNew { list { new(	Method	The mutation for creating the List.
input	Object	**Required.** The input parameter.

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Element			Type	Description
[payload: payload]			Object	**Required.** The actual values that need to be inserted.
	subType		String	The Subtype name .
	id		String	ID of the list.
	currentBaseState		String	For new records, the currentBaseState is DRAFT .
	currentSubState		String	For new records, the currentBaseState is DRAFT .
	data		Object	
		listTitle	String	**Required.** The title details of List.
		description	String	The description of the list.
		listEntities	-	-
			displayIdentifier	String	List of displayIdentifiers from workItem that must be linked with List.
		comments	Array of Objects	Contains comment text and attachment.
			commentText	String	Comment text.
			attachments	String of JSON Data	Attachment associated with the comment.
objectAction			-	For ListNew, the actionName is CREATE.
{ businessObjectIdentifier }			-	The BusinessObjectTypeNameand businesssObjectIdentifier(GUID) fields contain information of what data is newly inserted.

Example

```
mutation WorkItemNew {
  workItem {
    new(
      input: {
        workItem: {
          payload: {
            id: "6d211f5d-96bb-4bc2-8a27-006d517602da"
            currentBaseState: "Draft"
            data: {
              workItemTitle: "Missing product details"
              dueDate: 1747831980000
```

© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
              followers: [
                { followerId: "c55ff5ff-66d0-4c31-b2e4-5947a7e21955" }
              ]
              comments: [
                {
                  attachments: [
"{\"fileName\":\"test\",\"fileExtension\":\"rtf\",\"mimeType\":\"text/
rtf\",\"fileSize\":391,\"s3FileReference\":\"attachments/workItem/3728
7894-d3fe-42b7-8c1d-0dc36e5f4216\",\"fileStatus\":\"UPLOADED\"}"
                  ]
                  commentText: "Comment text from Peter while
creation"
                }
              ]
              assigneeCompany: {
                businessName: "QAPartnerCorp1202409240834280621"
                primaryIdentifierValue: "2054051864409"
                primaryIdentifierType: "GLN"
              }
              assigneeUser: {
                userName: "Marvin"
                userEmail: "qeauto+qapartnercorp1202409240834280621-
coa@tracelink.com"
              }
            }
          }
          objectAction: "UPDATE"
        }
      }
    ) {
      businessObjectTypeName
      businessObjectIdentifier
      businessObjectDataVersion
      mutateMessage
      isAsync
      asyncRequestDetails {
        requestIdentifier
        requestStatus
        consumerPollIntervalMS
        __typename
      }
      created {
        id
        objectTypeName
        dataVersion
        __typename
```

© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
      }
      updated {
        id
        objectTypeName
        dataVersion
        __typename
      }
      deleted {
        id
        objectTypeName
        dataVersion
        __typename
      }
      __typename
    }
    __typename
  }
}
```

Add list response

Guidelines



Element				Type	Description
Response				Method	-
data				Object	-
	list			-	-
		created		-	-
			id	-	GUID of newly inserted List.

Example

```
{
    "data": {
        "workItem": {
            "new": {
                "businessObjectTypeName": "workItem",
                "businessObjectIdentifier": "4fe82f69-605d-4608-a714-
fdc279e6dce5",
            }
        }
    }
}
```

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Errors

This app uses standard HTTP response codes. If an error occurs, additional available information regarding the cause of the error is provided in the **errMsg** element in the relevant response.

Edit list

Owners and Partners use this API to modify an existing list with new, updated, or corrected information (e.g. adding a description, updating the assignee company details, fixing a typo) and to update the workflow state (e.g. manually transitioning the base state from `Draft` to `ToDo` to indicate that the work assigned in the list has started).

Contact your TraceLink Services representative for more information about using this API.

Edit list request

Guidelines

Element	Type	Description
mutation ListEdit { list { edit(	Method	The mutation for updating the List.
input	Object	**Required.** The input parameter.
[payload: payload]	Object	**Required.** The values that need to be inserted.

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Element			Type	Description
subType			String	Subtype is non mandatory parameter when we are performing actions on Base Object. For Subtype it's mandatory to provide a Subtype name.
id			String	**Required.** The List GUID to update the exact record.
currentBaseState			String	Change the Workflow state from Draft to ToDo/InProgress/Done.
currentSubState			String	Change the Workflow state from Draft to ToDo/InProgress/Done.
data			Object	-
	listTitle		String	**Required.** Contains the title details of List.
	description		String	Change the description of the List.
	listEntities		Array of Objects	Contains the display identifier of the list.
		displayIdentifier	String	List of displayIdentifiers from workItem that must be linked with List.
	comments		Array of Objects	Contains comment text and attachment.
		commentText	String	Comment text.
		attachments	String of JSON Data	Attachment associated with the comment
objectAction			-	For listEdit, the actionName is UPDATE.
{ businessObjectIdentifier }			-	The BusinessObjectTypeName and businesssObjectIdentifier(GUID) fields contain information of what data is updated.

Example

```
mutation WorkItemEdit {
  workItem {
    edit(
```

© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
      input: {
        workItem: {
          payload: {
            id: "6d211f5d-96bb-4bc2-8a27-006d517602da"
            currentBaseState: "Draft"
            data: {
              workItemTitle: "Missing product details"
              dueDate: 1747831980000
              followers: [
                { followerId: "c55ff5ff-66d0-4c31-b2e4-5947a7e21955" }
              ]
              comments: [
                {
                  attachments: [
"{\"fileName\":\"test\",\"fileExtension\":\"rtf\",\"mimeType\":\"text/
rtf\",\"fileSize\":391,\"s3FileReference\":\"attachments/workItem/3728
7894-d3fe-42b7-8c1d-0dc36e5f4216\",\"fileStatus\":\"UPLOADED\"}"
                  ]
                  commentText: "Comment text from Peter while
creation"
                }
              ]
              assigneeCompany: {
                businessName: "QAPartnerCorp1202409240834280621"
                primaryIdentifierValue: "2054051864409"
                primaryIdentifierType: "GLN"
              }
              assigneeUser: {
                userName: "Marvin"
                userEmail: "qeauto+qapartnercorp1202409240834280621-
coa@tracelink.com"
              }
            }
          }
          objectAction: "UPDATE"
        }
      }
    ) {
      businessObjectTypeName
      businessObjectIdentifier
  }
}
```

Edit list response

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Guidelines

Element	Type	Description
Response	Method	-
data	Object	-
list	-	-
updated	-	-
id	-	GUID of newly updated WorkItem.

Example

```
{
    "data": {
        "workItem": {
            "edit": {
                "businessObjectTypeName": "workItem",
                "businessObjectIdentifier": "4fe82f69-605d-4608-a714-
fdc279e6dce5",
            }
        }
    }
}
```

Errors

This app uses standard HTTP response codes. If an error occurs, additional available information regarding the cause of the error is provided in the **errMsg** element in the relevant response.

Search list

Owners and Partners can use this API to search for a work item in the list. Provide a list of sort fields, page size, and paging info to search for a list.

Contact your TraceLink Services representative for more information about using this API.

Search list request

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Guidelines

Element		Type	Description
query ListSearch { list { search(		Method	The query for getting the details of the List
input		Object	**Required.** The input parameter.
	queryString	String	Contains the searching index and its values.
	sortFields	String	Sorting index array.
	pageSize	Integer	Page size in numeric.
	pagingInfo	String	Page information.
List of fields that you can pass on to Search method to fetch data			The fields provided in the view GraphQl query will be returned in the response if data is present in the list.
pagingInfo		-	-
documents		-	-

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Element			Type	Description
	id		String	**Required.** Enter the WorkItem GUID to update the exact record.
	currentBaseState		String	Current Base State Value.
	currentSubState		String	Current Sub Base State Value if Sub workFlows are activated.
	lastUpdatedDateTime		String	Last updated date time.
	lastUpdatedDateTimeFormatted		String	Last updated users GUID.
	data		Object	-
		currentState	String	This field contains the value of currentSubState if present, otherwise currentBaseState. That means currentState is ultimate State of the List.
		displayIdentifier	String	List identifier in readable format with Prefix-Counter (integer).
		listTitle	String	Title of the list.
		description	Integer	Description of the list.
		lastModifiedTimestamp	Integer	lastModifiedTimeStamp of List.
		lastModifiedTimestampFormatted	Date	lastModifiedTimeStampFormatted of lastModifiedTimeStamp from List.

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Example

```
query WorkItemSearch {
  workItem {
    search(
      input: {
        queryString: "(indexLuceneSubType:\"\" OR
indexLuceneSubType:null)"
        sortFields: [{ field: "index-lastUpdatedDateTime", sortAsc:
false }]
        pageSize: 3
        pagingInfo: ""
      }
    ) {
      pagingInfo
      documents {
        id
        currentBaseState
        currentSubState
        subType
        lastUpdatedDateTime
        lastUpdatedDateTimeFormatted
        data {
          currentState
          displayIdentifier
          workItemTitle
          dueDateFormatted
          initiatingCompany {
            businessName
          }
          assigneeCompany {
            businessName
          }
        }
      }
      facets {
        indexName
        path
        matchedDocsCount
        childFacetsCount
        childFacets {
          facetedName
          matchedDocsCount
        }
      }
    }
```

© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
  }
}
```

Search list response

Guidelines



			Element	Type	Description
Response				Method	-
data				Object	-
	list			-	-
		search		-	-
			pagingInfo	-	Page information if the current page is not the first one.
			documents	-	The details queried for the work item (e.g. display identifier, item title, current state, comments, followers, etc.).

Example

```
{
  "data": {
    "workItem": {
      "search": {
        "pagingInfo":
"eyJwYWdlSW5kZXgiOjEsInBhZ2luZ0luZm9LZXkiOm51bGx9",
        "documents": [
          {
            "id": "4fe82f69-605d-4608-a714-fdc279e6dce5",
            "currentBaseState": "Draft",
            "currentSubState": null,
            "subType": "",
```

© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
            "lastUpdatedDateTime": 1747227964874,
            "lastUpdatedDateTimeFormatted": "5/14/25, 1:06 PM (GMT)",
            "data": {
              "currentState": "Draft",
              "displayIdentifier": "WI-331",
              "workItemTitle": "ssss",
              "dueDateFormatted": "May 30, 2025, 12:59:00 PM (GMT)",
              "initiatingCompany": {
                "businessName": "QAOwnerCorp202409240834253301",
                "__typename":
"InitiatingCompanyLocationTypeDefinition"
              },
              "assigneeCompany": null,
              "__typename": "WorkItemData"
            },
            "__typename": "WorkItem"
          },
          {
            "id": "6d211f5d-96bb-4bc2-8a27-006d517602da",
            "currentBaseState": "Draft",
            "currentSubState": null,
            "subType": "",
            "lastUpdatedDateTime": 1747227496355,
            "lastUpdatedDateTimeFormatted": "5/14/25, 12:58 PM (GMT)",
            "data": {
              "currentState": "Draft",
              "displayIdentifier": "WI-330",
              "workItemTitle": "Missing product details",
              "dueDateFormatted": "May 21, 2025, 12:53:00 PM (GMT)",
              "initiatingCompany": {
                "businessName": "QAOwnerCorp202409240834253301",
                "__typename":
"InitiatingCompanyLocationTypeDefinition"
              },
              "assigneeCompany": {
                "businessName": "QAPartnerCorp1202409240834280621",
                "__typename": "BusinessCompanyLocationTypeDefinition"
              },
              "__typename": "WorkItemData"
            },
            "__typename": "WorkItem"
          },
          {
            "id": "4796f641-dba9-47b4-b8c6-b0acb41ed2c8",
            "currentBaseState": "Draft",
            "currentSubState": null,
```


© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
            "subType": "",
            "lastUpdatedDateTime": 1747135410051,
            "lastUpdatedDateTimeFormatted": "5/13/25, 11:23 AM (GMT)",
            "data": {
              "currentState": "Draft",
              "displayIdentifier": "WI-329",
              "workItemTitle": "rwer",
              "dueDateFormatted": "May 20, 2025, 11:23:14 AM (GMT)",
              "initiatingCompany": {
                "businessName": "QAOwnerCorp20240924083425330 1",
                "__typename":
"InitiatingCompanyLocationTypeDefinition"
              },
              "assigneeCompany": null,
              "__typename": "WorkItemData"
            },
            "__typename": "WorkItem"
          }
        ],
        "facets": [],
        "__typename": "WorkItemSearchResult"
      },
      "__typename": "WorkItemQueryOps"
    }
  }
}
```


Errors

This app uses standard HTTP response codes. If an error occurs, additional available information regarding the cause of the error is provided in the **errMsg** element in the relevant response.

Delete list

Owners use this API to delete a work item that is no longer required. Provide the work item identifier in the input field and the current base state to delete a work item.

Contact your TraceLink Services representative for more information about using this API.

Delete list request

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Guidelines

Element		Type	Description
mutation ListDelete { list { delete(		Method	The mutation for deleting the List.
input		Object	**Required.** The input parameter.
	id	String	**Required.** The List GUID to update the exact record.
{ businessObjectIdentifier }		-	The BusinessObjectTypeName and businesssObjectIdentifier (GUID) fields contain information of what data is updated.

Example

```
mutation WorkItemDelete {
  workItem {
    delete(input: { id: "4fe82f69-605d-4608-a714-fdc279e6dce5" }) {
      businessObjectTypeName
      businessObjectIdentifier
    }
    __typename
  }
}
```

Delete list response

Guidelines

Element	Type	Description
Response	Method	-
data	Object	-

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Element	Type	Description
list	-	-
deleted	-	-
id	-	GUID of deleted list.
displayIdentifier	-	Readable Identifier which is used with configured prefix value (Eg: POET-111).

Example

```
{
    "data": {
        "workItem": {
            "delete": {
                "businessObjectTypeName": "workItem",
                "businessObjectIdentifier": "4fe82f69-605d-4608-a714-
fdc279e6dce5",
            }
        }
    }
}
```

Errors

This app uses standard HTTP response codes. If an error occurs, additional available information regarding the cause of the error is provided in the **errMsg** element in the relevant response.

Follow list

Owners and Partners use this API to start following a work item. Provide the item identifier to start following the work item.

Contact your TraceLink Services representative for more information about using this API.

Follow list request

Guidelines

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Element		Type	Description
mutation ListStartFollow { list { startFollow(		Method	The mutation for updating List followers list.
input		object	**Required.** The input parameter.
	id	String	**Required.** The List GUID to update the exact record.
{ businessObjectIdentifier }		-	The BusinessObjectTypeName and businesssObjectIdentifier(GUID) fields contain information of what data is updated.

Example

```
mutation WorkItemStartFollow {
  workItem {
    startFollow(input: {id: "2335af1c-4193-469d-b9c2-61400032f74e"}) {
      businessObjectTypeName
      businessObjectIdentifier
      businessObjectDataVersion
      mutateMessage
      isAsync
      updated {
        id
        objectTypeName
        dataVersion
        __typename
      }
      __typename
    }
    __typename
  }
}
```

Follow list response

Guidelines

Element	Type	Description
Response	Method	-
data	Object	-

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Element				Type	Description
	list			-	-
		updated		-	-
			id	-	GUID of newly updated List.
			displayIdentifier	-	Readable Identifier which is used with configured prefix value (Eg: POET-111).

Example

```
{
    "data": {
        "workItem": {
            "startFollow": {
                "businessObjectTypeName": "workItem",
                "businessObjectIdentifier": "d972e6ec-5ec7-4d81-
ac13-41aa40e60e64",
                "businessObjectDataVersion": 4,
                "mutateMessage": "Successfully followed the Work
Item",
                "isAsync": null,
                "updated": [
                    {
                        "id": "d972e6ec-5ec7-4d81-ac13-41aa40e60e64",
                        "objectTypeName": "workItem",
                        "dataVersion": 4,
                        "__typename":
"MutateOperationResultEntryTypeDef"
                    }
                ],
                "__typename": "MutateOperationResultTypeDef"
            },
            "__typename": "WorkItemMutationOps"
        }
    }
}
```

Errors

This app uses standard HTTP response codes. If an error occurs, additional available information regarding the cause of the error is provided in the **errMsg** element in the relevant response.

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Unfollow list

Owners and Partners use this API to stop following a work item. Provide the work item identifier to stop following a work item.

Contact your TraceLink Services representative for more information about using this API.

Unfollow list request

Guidelines

Element		Type	Description
mutation ListStopFollow { list { stopFollow(		Method	The mutation for updating the List followers list.
input		Object	**Required.** The input parameter.
	id	String	**Required.** The WorkItem GUID to update the exact record.
{ businessObjectIdentifier }		-	The BusinessObjectTypeName and businesssObjectIdentifier(GUID) fields contain information of what data is updated.

Example

```
mutation WorkItemStopFollow {
  workItem {
    stopFollow(input: {id: "2335af1c-4193-469d-b9c2-61400032f74e"}) {
      businessObjectTypeName
      businessObjectIdentifier
      businessObjectDataVersion
      mutateMessage
      isAsync
      updated {
        id
        objectTypeName
        dataVersion
        __typename
      }
      __typename
    }
    __typename
```

© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
  }
}
```

Unfollow list response

Guidelines



Element				Type	Description
Response				Method	-
data				Object	-
	list			-	-
		new		-	-
			id	-	GUID of newly updated List
			displayIdentifier	-	Readable Identifier which is used with configured prefix value (Eg: POET-111)

Example

```
{
    "data": {
        "workItem": {
            "stopFollow": {
                "businessObjectTypeName": "workItem",
                "businessObjectIdentifier": "d972e6ec-5ec7-4d81-
ac13-41aa40e60e64",
                "businessObjectDataVersion": 3,
                "mutateMessage": "Successfully unfollowed the Work
Item",
                "isAsync": null,
                "updated": [
                    {
                        "id": "d972e6ec-5ec7-4d81-ac13-41aa40e60e64",
                        "objectTypeName": "workItem",
                        "dataVersion": 3,
                        "__typename":
"MutateOperationResultEntryTypeDef"
                    }
                ],
                "__typename": "MutateOperationResultTypeDef"
            },
            "__typename": "WorkItemMutationOps"
        }
    }
```

© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
}
```

Errors

This app uses standard HTTP response codes. If an error occurs, additional available information regarding the cause of the error is provided in the **errMsg** element in the relevant response.

View list

Owners and Partners use this API to view an item. Provide the item identifier to view an item.

Contact your TraceLink Services representative for more information about using this API.

View list request

Guidelines

Element	Type	Description
query ListView { list { view(	Method	The query for getting details of the List.
input	Object	**Required.** The input parameter.
id	String	**Required.**The List GUID to update the exact record.
List of fields that you can pass on to View method to fetch data	-	The fields provided in the view GraphQl query will be returned in the response if data is present in the list.
id	String	GUID of List.
currentBaseState	String	Current Base State Value.
currentSubState	String	Current Sub Base State Value if Sub workflows are activated.
lastUpdatedDateTime	Integer	Last updated date time.
lastUpdatedDateTimeFormatted	String	Last updated users GUID.
data	Object	-

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Element		Type	Description
currentState		String	This field will hold value of currentSubState if present, otherwise currentBaseState. So, currentState is ultimate State of the List.
displayIdentifier		String	List identifier in readable format with Prefix-Counter (integer).
workItemTitle		String	Title of the list.
dueDate		Integer	Due date of the list.
dueDateFormatted		String	Formatted value of due in readable format.
creationTimestamp		DateTime	Creation date time in milliseconds.
creationTimestampFormatted		DateTime	Creation date time in readable format.
lastModifiedTimestamp		DateTime	Last modified date time in milliseconds.
lastModifiedTimestampFormatted		DateTime	Last modified date time in readable format.
createdByUser		Object	Contains details of the user who created the work item.
	userName	String	User's name who created the workitem.
	userEmail	String	User's email who created the workitem.
lastModifiedByUser		Object	Contains details of the user who modified the work item.
	userName	String	User's name who last updated the workitem.
	userEmail	Integer	User's email who last updated the workitem.
initiatingCompany		Object	Contains the initiating company name, identifier type, and identifier value.
	primaryIdentifierType	String	Primary Identifier Type of Initiating company.
	primaryIdentifierValue	String	Primary Identifier Value of Initiating company.
	businessName	String	Business name of Initiating Company.
assigneeCompany		Object	Contains the assignee company name, identifier type, and identifier value.
	primaryIdentifierType	String	Primary Identifier Type of assignee company.
	primaryIdentifierValue	String	Primary Identifier Value of assignee company.
	businessName	String	Business name of assignee Company.
followers		Object	Contains the follower IDs.
	followerId	String	Following users GUID.

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Example

```
query WorkItemView {
  workItem {
    view(input: {id: "d972e6ec-5ec7-4d81-ac13-41aa40e60e64"}) {
      id
      currentBaseState
      currentSubState
      lastUpdatedDateTime
      lastUpdatedDateTimeFormatted
      data {
        currentState
        comments {
          commentIdentifier
          commentText
          attachments
          attachmentsFormatted
          commentedDateTime
          commentedDateTimeFormatted
          commentAuthorId
          commentAuthorIdFormatted
          __typename
        }
        displayIdentifier
        initiatingCompany {
          primaryIdentifierType
          primaryIdentifierValue
          businessName
          __typename
        }
        assigneeCompany {
          primaryIdentifierType
          primaryIdentifierValue
          businessName
          __typename
        }
        workItemTitle
        dueDate
        dueDateFormatted
        followers {
          followerId
          followerIdFormatted
          __typename
        }
        __typename
      }
```

© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
      __typename
    }
    __typename
  }
}
```

View list response

Guidelines

Element	Type	Description
Response	Method	-
data	Object	-

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Element	Type	Description
workItem	-	-
view	-	-
id	String	GUID of WorkItem.
currentBaseState	String	Current Base State Value.
currentSubState	String	Current Sub Base State Value if Sub workflows are activated.
lastUpdatedDateTime	Integer	Last updated date time.
lastUpdatedDateTimeFormatted	String	Last updated users GUID.
data	Object	-
currentState	String	This field will hold value of currentSubState if present, otherwise currentBaseState. So, currentState is ultimate State of the WorkItem.
displayIdentifier	String	WorkItem identifier in readable format with Prefix-Counter (integer).
workItemTitle	String	Title of the workItem.
dueDate	Integer	Due date of the workItem.
dueDateFormatted	String	Formatted value of due in readable format.
creationTimestamp	DateTime	Creation date time in milliseconds.
creationTimestampFormatted	DateTime	Creation date time in readable format.
lastModifiedTimestamp	DateTime	Last modified date time in milliseconds.
lastModifiedTimestampFormatted	DateTime	Last modified date time in readable format.
createdByUser	Object	Contains details of the user who created the work item.
userName	String	User's name who created the workitem.
userEmail	String	User's email who created the workitem.
lastModifiedByUser	Object	Contains details of the user who modified the work item.
userName	String	User's name who last updated the workitem.
userEmail	Integer	User's email who last updated the workitem.
initiatingCompany	Object	Contains the initiating company name, identifier type, and identifier value.
primaryIdentifierType	String	Primary Identifier Type of Initiating company.
primaryIdentifierValue	String	Primary Identifier Value of Initiating company.
businessName	String	Business name of Initiating Company.
assigneeCompany	Object	Contains the assignee company name, identifier type, and identifier value.
primaryIdentifierType	String	Primary Identifier Type of assignee company.
primaryIdentifierValue	String	Primary Identifier Value of assignee company.
businessName	String	Business name of assignee Company.
followers	Object	Contains the follower IDs.
followerId	String	Following users GUID.

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Example


```
{
    "data": {
        "workItem": {
            "view": {
                "id": "d972e6ec-5ec7-4d81-ac13-41aa40e60e64",
                "currentBaseState": "ToDo",
                "currentSubState": null,
                "lastUpdatedDateTime": 1734860500367,
                "lastUpdatedDateTimeFormatted": "12/22/24, 9:41 AM
(GMT)",
                "data": {
                    "currentState": "ToDo",
                    "comments": [
                        {
                            "commentIdentifier": "ac067728-
ce20-437a-8c8e-bb305067eda3",
                            "commentText": "Added by partner",
                            "attachments": [
"{\"fileName\":\"Original_File\",\"fileExtension\":\"txt\",\"mimeType\
":\"text/plain\",\"fileSize\":10,\"s3FileReference\":\"attachments/wor
kItem/1eb0ddfc-a11b-4567-
a929-55d3ef4d2d1f\",\"fileStatus\":\"UPLOADED\"}"
                            ],
                            "attachmentsFormatted": [
                                "Original_File.txt (10 bytes)"
                            ],
                            "commentedDateTime": 1734600804941,
                            "commentedDateTimeFormatted": "Dec 19,
2024, 9:33:24 AM (GMT)",
                            "commentAuthorId": "a3ef9f60-0276-11ed-
ad1d-0242ac110011",
                            "commentAuthorIdFormatted": "Kaushal
Lavate",
                            "__typename": "CommentTypeDefinition"
                        }
                    ],
                    "displayIdentifier": "WI-79",
                    "initiatingCompany": {
                        "primaryIdentifierType": "GLN",
                        "primaryIdentifierValue": "2054051864409",
                        "businessName":
"QAPartnerCorp1202409240834280621",
                        "__typename":
"InitiatingCompanyLocationTypeDefinition"
```


© TraceLink Inc. 2009 - 2025 All Rights Reserved

```
                    },
                    "assigneeCompany": {
                        "primaryIdentifierType": "GLN",
                        "primaryIdentifierValue": "4700421709532",
                        "businessName":
"QAOwnerCorp202409240834253301",
                        "__typename":
"BusinessCompanyLocationTypeDefinition"
                    },
                    "workItemTitle": "Added by partner",
                    "dueDate": 1735205467366,
                    "dueDateFormatted": "Dec 26, 2024, 9:31:07 AM
(GMT)",
                    "followers": [
                        {
                            "followerId": "a3ef9f60-0276-11ed-
ad1d-0242ac110011",
                            "followerIdFormatted": "Matt Damon",
                            "__typename":
"WorkItemFollowersTypeDefinition"
                        },
                        {
                            "followerId": "c55ff5ff-66d0-4c31-
b2e4-5947a7e21955",
                            "followerIdFormatted": "Patricia
Reynolds",
                            "__typename":
"WorkItemFollowersTypeDefinition"
                        }
                    ],
                    "__typename": "WorkItemData"
                },
                "__typename": "WorkItem"
            },
            "__typename": "WorkItemQueryOps"
        }
    }
}
```


Errors

This app uses standard HTTP response codes. If an error occurs, additional available information regarding the cause of the error is provided in the **errMsg** element in the relevant response.

© TraceLink Inc. 2009 - 2025 All Rights Reserved

Related Content



Forecast plan (IDoc)

Forecasting APIs allow companies to exchange data about anticipated product demand and supply availability with upstream supply chain Partners without giving these Partners access to their serialization system of record.

View More



Forecast plan (X12)

Forecasting APIs allow companies to exchange data about anticipated product demand and supply availability with upstream supply chain Partners without giving these Partners access to their serialization system of record.

View More



Forecast plan response (IDoc)

Forecasting APIs allow companies to exchange data about anticipated product demand and supply availability with downstream supply chain Partners without giving these Partners access to their serialization system of record.

View More

© TraceLink Inc. 2009 - 2025 All Rights Reserved